




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B25C 1/04, A41H 37/02	A2	(11) International Publication Number: WO 98/43781 (43) International Publication Date: 8 October 1998 (08.10.98)
(21) International Application Number: PCT/US98/05909 (22) International Filing Date: 24 March 1998 (24.03.98) (30) Priority Data: 97/03847 28 March 1997 (28.03.97) FR (71) Applicant (for all designated States except US): SENSOR-MATIC ELECTRONICS CORPORATION (US/US); 951 Yamato Road, Boca Raton, FL 33431-0700 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): GOUELIBO, Didier [FR/FR]; 3, rue de Bourgneuf, F-78720 Cernay-la-Ville (FR). DAMEME, Alain [FR/FR]; 10, rue Saint Nicolas, F-78640 Neauphle-le-Château (FR). (74) Agent: LEVIN, Nathaniel; Robin, Blecker & Daley, 330 Madison Avenue, New York, NY 10017 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Eurasian patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: SEMI-AUTOMATIC APPARATUS FOR AFFIXING AN ANTI-THEFT DEVICE TO AN ARTICLE



(57) Abstract

A semi-automatic machine for affixing an anti-theft device, such as an EAS marker, to an article of clothing or the like. The anti-theft device is of the type made up of two elements that are to be snapped together through the article of clothing. Each of the two kinds of elements is stored in a respective vibrating bowl and transferred to an assembly station by a respective vibrating conveyor. One of the two elements is positioned on a working surface at the assembly station. The second element is taken up by a snap-connection mechanism. A laser provides a reference mark at the working surface so that an operator can precisely position a desired part of the article of clothing for receiving the anti-theft device. After the article is positioned in accordance with the reference mark, the snap-connection mechanism is actuated to insert the second element into the first element through the article of clothing.

09381752-092209